Xuanyang M&E Equipment (Shanghai) Co,. Ltd Room 1010, New Century Building, Lujiabang Road, Shanghai 200011

Tel: 021-6376 1198 Fax: 021-6376 0778 Email: hsy@xytec.net Website: www.xytec.net

02.5

The 2.5 kN Q2.5 is the Universal Testing Machine with the state-of-the-art design, built to the highest quality levels and with many advanced technical features.

Programming tests and monitoring results can be controlled through our powerful and intelligent Graphwork 5.0 test software, which allow complete and accurate data management in accordance with European, North American and International Standards.

This instrument is suitable for use both in production lines where the operator has to be fast and efficient and can accurately control the test with the optional remote control unit, and also laboratory environments where the advanced software lets users analyse the test data. Graphwork allows full control of processing, filing, managing, and transmitting data to the company network, database, and performs many other functions.

This Q2.5 frame has a flexible and modular construction. It can be equipped with various grips and fixtures, as well as extensometers, additional load cells, temperature chambers and many more accessories, for a wide range of applications (tensile, compression, flexure, etc.).

In addition, this user-friendly instrument can be fitted with additional load cells with lower capacities, providing the highest resolution and accuracy for micro-loads.

Technical specifications

Frame Capacity 2.5 kN (550 lbf)

Standards met or exceeded ASTM E4,EN-ISO 7500/1

Load reading resolution 1/30000 f.s.

Stroke resolution 1 micron

Speed at maximum load 0,1-1000 mm/min. Idle speed 1000 mm/min.

Controlled total stroke 750 mm (30 in.)

Maximum daylight between connecting adapters 750 mm (30 in.) Free daylight of machine upright axis 100 mm (4 in.)

Power supply 230V/1ph/50Hz or 120V/1ph/60Hz

Power consumption 350 W

Machine weight (without accessories)

46 Kg (100 lb)

Dimensions:

 Height
 1140 mm (44,5 in.)

 Width
 550 mm (21,5 in.)

 Depth
 460 mm (18 in.)

Depth 460 mm (18 in.) Paint:

Fixed parts Silver RAL 9006 /Black RAL 9011

Moving parts Black RAL 9011

 Single-column rigid system with 2.5 kN maximum capacity Suitable for plastics, textile, composites and other materials

- Stylish design and advanced features
- Two-Year Warranty
- Flexible and modular design for easy future expansion
- Key technical advantages include extremely high resolution af load and stroke readings for the high performance and most accurate results
- Manufactured by an ISO 9001 certified company
- Excellent price-to-quality ratio

